

# CURTAIN DETECTORS

## DT16

EN 50131-2-4 / GRADE 2

Dual technology detector, infrared and microwave at 24 Ghz

Order Codes:

**DT 16:**

white colour

**DT 16-M:**

dark brown colour



## IF16/L


EN 50131-2-2 / GRADE 2

Passive infrared detector with high power LED

Order Code:

**IF 16/L:**

white colour



Buzzer with different sounds depending on the direction of the movement



	DT 16	IF 16/L
EN 50131-2-4 / GRADE 2	YES	-
EN 50131-2-2 / GRADE 2	-	YES
RANGE	from 2 to 3,5 mt	from 2 to 3,5 mt
ANGLE	165°	165°
CURTAIN LENS ORIENTATION	YES	YES
ALARM TIME	4"	4"
PROGRAMMABLE ALARM DELAY	-	YES
HIGH POWER LED FOR LIGHTING AND/OR ALARM	-	YES
WALK TEST'S LED	YES	YES
ALARM DIRECTION RECOGNITION	YES	YES
DOUBLE SOUND BUZZER (ENTRANCE/EXIT)	-	YES
ANTI-OPENING TAMPER	YES	YES
RFI PROTECTION	30 V/m	30 V/m
TEMPERATURE COMPENSATION	YES	YES
POWER SUPPLY	10 - 15 Vdc	10 - 15 Vdc
CONSUMPTION IN STAND BY	18 mA	12 mA
HOUSING	ABS	ABS
PROTECTION CLASS	IP 54	IP 54
OPERATING TEMPERATURE	from -25°C to +55°C	from -25°C to +55°C
DIMENSIONS	37 x 130 x 37 mm	37 x 130 x 37 mm



Detectors able to create a protective "curtain" barrier useful for doors and windows.

✳ Angle 165°

✳ Adjustable range from 2 to 3,5 mt